NSN 5915-00-855-4472

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-855-4472

Overall Length:

- 2.375 inches
- **Overall Height:**
- 1.250 inches

Overall Width:

1.969 inches

Body Length:

1.438 inches

Body Width:

1.531 inches

Unthreaded Mounting Hole Diameter:

0.938 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.938 inches

Operating Tempurature Range:

+0.0/+90.0 degrees celsius

Reference Frequency Per Function:

4.0 kilohertz blank

Input Impedance Per Function W/load:

1.0 kilohms blank

Output Impedance Per Function W/source Across Input:

50.0 kilohms blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.5 blank

Functional Terminal Type And Quantity:

2 turret ground 3rd function

Specified Frequencies Of Discrimination Per Function:

0.00 hertz blank and 8.00 kilohertz blank and 14.00 kilohertz blank and 600.00 kilohertz blank

Body Material:

Metal

Frequency Band Width Per Function:

0.00 hertz blank and 8.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

 $0.5\,$ blank and $3.0\,$ blank and $60.0\,$ blank and $60.0\,$ blank

Maximum Dielectric Withstanding Dc Voltage:

1.0 kilovolts at sea level

NSN 5915-00-855-4472

Low Pass Filter - Page 2 of 2



Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0