## NSN 5915-00-856-9405

**Maximum Dielectric Withstanding Dc Voltage:** 

1.0 kilovolts at sea level

Special Features:

Terminals on one surface

Low Pass Filter - Page 1 of 2

Overall Length: 2.250 inches Overall Height: 2.500 inches Body Length:



View Online at https://aerobasegroup.com/nsn/5915-00-856-9405

1.250 inches
Body Width:
1.250 inches
Body Height:
2.250 inches
Unthreaded Mounting Hole Diameter:
Between 0.169 inches and 0.177 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.875 inches
Operating Tempurature Range:
+0.0/+75.0 degrees celsius
Reference Frequency Per Function:
3.1 kilohertz blank
Input Impedance Per Function W/load:
1.0 kilohms blank
Output Impedance Per Function W/source Across Input:
10.0 kilohms blank
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
2 unthreaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
1.0 blank
Functional Terminal Type And Quantity:
1 tab, solder lug output 2nd function
Specified Frequencies Of Discrimination Per Function:
2.00 kilohertz blank and 4.20 kilohertz blank and 14.00 kilohertz blank and 28.00 kilohertz blank
Body Material:
Metal
Frequency Band Width Per Function:
2.00 kilohertz blank and 4.20 kilohertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:
1.0 blank and 1.0 blank and 60.0 blank and 60.0 blank

## NSN 5915-00-856-9405

Low Pass Filter - Page 2 of 2



Style Designator:
Rectangular terminal/terminals on opposite surfaces
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A047b0