## NSN 5915-00-860-5702

High Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-860-5702

Overall Height:
2.250 inches
Body Length:
4.375 inches
Body Width:
2.375 inches
Body Height:
1.906 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
3.688 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.688 inches
Operating Tempurature Range:
+0.0/+65.0 degrees celsius
Average Life Rating In Hours:
14400.0
Reference Frequency Per Function:
2.0039 megahertz blank
Source Impedance Rating Per Function:
6.8 kilohms blank
Input Impedance Per Function W/load:
6.8 kilohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
2.0 blank
Functional Terminal Type And Quantity:
1 turret output 2nd function
Specified Frequencies Of Discrimination Per Function:
1.9997 megahertz blank and 2.0003 megahertz blank and 2.0075 megahertz blank and 2.0081 megahertz blank
Thread Size:
0.138 inches
Frequency Band Width Per Function:
2.0003 megahertz blank and 2.0075 megahertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:
50.0 blank and 2.0 blank and 50.0 blank
Style Designator:

Rectangular terminal/terminals on one surface

## NSN 5915-00-860-5702

High Pass Filter - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0