NSN 5915-00-862-6706

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-862-6706

| Overall Length: |
|---|
| 1.125 inches |
| Overall Height: |
| 0.563 inches |
| Overall Width: |
| 0.812 inches |
| Body Length: |
| 1.000 inches |
| Body Width: |
| 0.812 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.093 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 0.444 inches |
| Operating Tempurature Range: |
| -10.0/+75.0 degrees celsius |
| Reference Frequency Per Function: |
| 5.6 kilohertz blank |
| Source Impedance Rating Per Function: |
| 50.0 ohms blank |
| Load Impedance Per Function: |
| 50.0 ohms blank |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole |
| Insertion Loss At Reference Frequency Per Function In Decibels: |
| 6.0 blank |
| Functional Terminal Type And Quantity: |
| 1 turret output 2nd function |
| Specified Frequencies Of Discrimination Per Function: |
| 5.45 kilohertz blank and 5.75 kilohertz blank and 10.90 kilohertz blank and 16.35 kilohertz blank |
| Frequency Band Width Per Function: |
| 5.45 kilohertz blank and 5.75 kilohertz blank |
| Discrimination At Specificationified Frequencies Per Function In Decibels: |
| 0.0 blank and 6.0 blank and 20.0 blank and 35.0 blank |
| Style Designator: |
| Rectangular terminal/terminals on adjacent surfaces |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5915-00-862-6706

Low Pass Filter - Page 2 of 2



Demilitarization:

No

Fiig:

A047b0