## NSN 5915-00-866-5375

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-866-5375

Overall Height:
3.344 inches
Body Length:
2.531 inches
Body Width:
1.922 inches
Body Height:
2.969 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.125 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.531 inches
Operating Tempurature Range:
-40.0/+55.0 degrees celsius
Reference Frequency Per Function:
2.975 kilohertz blank
Input Impedance Per Function W/load:
600.0 ohms blank
Output Impedance Per Function W/source Across Input:
600.0 ohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Unc Inclosure Type:
Inclosure Type:
Inclosure Type: Hermetically sealed
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 12.0 blank
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 12.0 blank Functional Terminal Type And Quantity:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 12.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle input-output/ground
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 12.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle input-output/ground Maximum Dielectric Withstanding Ac Rms Voltage:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 12.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle input-output/ground Maximum Dielectric Withstanding Ac Rms Voltage: 500.0 volts at sea level
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 12.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle input-output/ground Maximum Dielectric Withstanding Ac Rms Voltage: 500.0 volts at sea level Specified Frequencies Of Discrimination Per Function:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 12.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle input-output/ground Maximum Dielectric Withstanding Ac Rms Voltage: 500.0 volts at sea level Specified Frequencies Of Discrimination Per Function: 2.715 kilohertz blank and 2.895 kilohertz blank and 3.055 kilohertz blank and 3.235 kilohertz blank
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 12.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle input-output/ground Maximum Dielectric Withstanding Ac Rms Voltage: 500.0 volts at sea level Specified Frequencies Of Discrimination Per Function: 2.715 kilohertz blank and 2.895 kilohertz blank and 3.055 kilohertz blank and 3.235 kilohertz blank Thread Size:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 12.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle input-output/ground Maximum Dielectric Withstanding Ac Rms Voltage: 500.0 volts at sea level Specified Frequencies Of Discrimination Per Function: 2.715 kilohertz blank and 2.895 kilohertz blank and 3.055 kilohertz blank and 3.235 kilohertz blank Thread Size: 0.164 inches
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 12.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle input-output/ground Maximum Dielectric Withstanding Ac Rms Voltage: 500.0 volts at sea level Specified Frequencies Of Discrimination Per Function: 2.715 kilohertz blank and 2.895 kilohertz blank and 3.055 kilohertz blank and 3.235 kilohertz blank Thread Size: 0.164 inches Body Material:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 12.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle input-output/ground Maximum Dielectric Withstanding Ac Rms Voltage: 500.0 volts at sea level Specified Frequencies Of Discrimination Per Function: 2.715 kilohertz blank and 2.895 kilohertz blank and 3.055 kilohertz blank and 3.235 kilohertz blank Thread Size: 0.164 inches Body Material: Metal

40.0 blank and 1.5 blank and 40.0 blank

## NSN 5915-00-866-5375

Band Pass Filter - Page 2 of 2



Style	Design	ator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0