

View Online at <https://aerobasegroup.com/nsn/5915-00-867-5678>

Body Length:

4.500 inches

Body Width:

4.000 inches

Body Height:

1.500 inches

Operating Temperature Range:

-30.0/+55.0 degrees celsius

Reference Frequency Per Function:

250.0 7th high pass two phase to three phase

Input Impedance Per Function W/load:

1.0 kilohms 4th low pass

Output Impedance Per Function W/source Across Input:

1.0 kilohms 4th low pass

Principal Circuitry Type Per Function:

Inductance-capacitance 3rd low pass

Input Terminal Manufacturer Code:

64959

Input Terminal Identification:

G30283

Output Terminal Manufacturer Code:

64959

Output Terminal Identification:

G30283

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 4th low pass

Functional Terminal Type And Quantity:

4 connector, receptacle input 1st function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz 4th low pass and 500.00 hertz 4th low pass and 700.00 hertz 4th low pass and 1.40 kilohertz 4th low pass

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.00 hertz 2nd low pass and 500.00 hertz 2nd low pass

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 4th low pass and 1.0 4th low pass and 26.0 4th low pass and 26.0 4th low pass

Body Surface Treatment:

Tin

Special Features:

Secondary mounting facility, two 0.164-32 unc threaded holes

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0