

View Online at <https://aerobasegroup.com/nsn/5915-00-867-5678>

**Body Length:**

4.500 inches

**Body Width:**

4.000 inches

**Body Height:**

1.500 inches

**Operating Temperature Range:**

-30.0/+55.0 degrees celsius

**Reference Frequency Per Function:**

250.0 7th high pass two phase to three phase

**Input Impedance Per Function W/load:**

1.0 kilohms 4th low pass

**Output Impedance Per Function W/source Across Input:**

1.0 kilohms 4th low pass

**Principal Circuitry Type Per Function:**

Inductance-capacitance 3rd low pass

**Input Terminal Manufacturer Code:**

64959

**Input Terminal Identification:**

G30283

**Output Terminal Manufacturer Code:**

64959

**Output Terminal Identification:**

G30283

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

1.0 4th low pass

**Functional Terminal Type And Quantity:**

4 connector, receptacle input 1st function

**Specified Frequencies Of Discrimination Per Function:**

1.00 hertz 4th low pass and 500.00 hertz 4th low pass and 700.00 hertz 4th low pass and 1.40 kilohertz 4th low pass

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.00 hertz 2nd low pass and 500.00 hertz 2nd low pass

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

1.0 4th low pass and 1.0 4th low pass and 26.0 4th low pass and 26.0 4th low pass

**Body Surface Treatment:**

Tin

**Special Features:**

Secondary mounting facility, two 0.164-32 unc threaded holes

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0