

View Online at <https://aerobasegroup.com/nsn/5915-00-867-5841>

Overall Height:

2.270 inches

Body Length:

2.010 inches

Body Width:

0.690 inches

Body Height:

2.010 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.156 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Operating Temperature Range:

-54.0/+71.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

1.65 kilohertz blank

Input Impedance Per Function W/load:

600.0 ohms blank

Output Impedance Per Function W/source Across Input:

600.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Average Power Rating Per Function:

0.5 watts blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

3 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

0.5 blank

Functional Terminal Type And Quantity:

1 turret output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

100.0 volts at altitude and 100.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

300.00 hertz blank and 3.00 kilohertz blank and 5.00 kilohertz blank and 20.00 kilohertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

300.00 hertz blank and 3.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 23.0 blank and 23.0 blank

Unpackaged Unit Weight:

1.0000 pounds

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0