

View Online at <https://aerobasegroup.com/nsn/5915-00-867-5841>

**Overall Height:**

2.270 inches

**Body Length:**

2.010 inches

**Body Width:**

0.690 inches

**Body Height:**

2.010 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.156 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Operating Temperature Range:**

-54.0/+71.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

1.65 kilohertz blank

**Input Impedance Per Function W/load:**

600.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

600.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Average Power Rating Per Function:**

0.5 watts blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

3 threaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

0.5 blank

**Functional Terminal Type And Quantity:**

1 turret output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

100.0 volts at altitude and 100.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

300.00 hertz blank and 3.00 kilohertz blank and 5.00 kilohertz blank and 20.00 kilohertz blank

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

300.00 hertz blank and 3.00 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

1.0 blank and 23.0 blank and 23.0 blank

**Unpackaged Unit Weight:**

1.0000 pounds

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0