

View Online at <https://aerobasegroup.com/nsn/5915-00-876-6594>

Overall Length:

1.288 inches

Body Length:

0.312 inches

Body Outside Diameter:

Between 0.338 inches and 0.348 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Average Life Rating In Hours:

250.0

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Power Line Frequency Rating Per Function In Hertz:

400.0 blank

Operating Current Rating Per Function In Amps:

10.0 blank

Maximum Voltage Drop Per Function:

0.5 volts dc blank

Principal Circuitry Type Per Function:

Inductance-capacitance, mounting end blank

Full Load Insertion Loss Frequencies In Megahertz:

0.03 and 0.15 and 1.0 and 10.0 and 100.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

7.0 and 21.0 and 37.0 and 57.0 and 70.0 and 70.0

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Nut and washer

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Operating Voltage Rating And Type Per Function:

5.0 volts ac blank and 50.0 volts dc blank

Thread Size:

0.250 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

100.0 volts at sea level

Body Surface Treatment:

Silver

Precious Material And Location:

Body and contact surfaces silver

Precious Material:

Silver

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0