NSN 5915-00-878-9867

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-878-9867

Overall Length: 3.368 inches

Body Length:

Between 2.031 inches and 2.093 inches

Body Outside Diameter:

Between 0.719 inches and 0.783 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Operating Tempurature Range:

-35.0/+95.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

2.75 megahertz blank

Input Impedance Per Function W/load:

91.0 ohms blank

Output Impedance Per Function W/source Across Input:

91.0 ohms blank

Input Terminal Manufacturer Code:

80058

Input Terminal Identification:

Ug-1619/u

Output Terminal Manufacturer Code:

80058

Output Terminal Identification:

Ug-1094/u

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

1 threaded bushing

Insertion Loss At Reference Frequency Per Function In Decibels:

0.5 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.00 megahertz blank and 5.50 megahertz blank and 88.00 megahertz blank and 1.00 gigahertz blank

Thread Size:

0.500 inches

Frequency Band Width Per Function:

1.00 megahertz blank and 5.50 megahertz blank

NSN 5915-00-878-9867

Low Pass Filter - Page 2 of 2



Discrimination At Specificationified Frequencies Per Function In Decibels

3.0 blank and 3.0 blank and 70.0 blank and 80.0 blank

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0