## NSN 5915-00-879-0448



Low Pass Filter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5915-00-879-0448 **Overall Length:** 3.368 inches **Body Length:** Between 2.031 inches and 2.093 inches **Body Outside Diameter:** Between 0.719 inches and 0.781 inches Vibration Resistance Range In Hertz: +10.0/+55.0 **Operating Tempurature Range:** -35.0/+95.0 degrees celsius **Average Life Rating In Hours:** 10000.0 **Reference Frequency Per Function:** 2.75 megahertz blank Input Impedance Per Function W/load: 91.0 ohms blank **Output Impedance Per Function W/source Across Input:** 91.0 ohms blank **Input Terminal Manufacturer Code:** 80058 **Input Terminal Identification:** 

Ug-1094/u

**Output Terminal Manufacturer Code:** 

80058

**Output Terminal Identification:** 

Ug-1619/u

**Mounting Facility Screw Thread Series Designator:** 

Unef

**Inclosure Type:** 

Encased

**Mounting Facility Type And Quantity:** 

1 threaded bushing

Insertion Loss At Reference Frequency Per Function In Decibels:

0.5 blank

**Functional Terminal Type And Quantity:** 

1 connector, receptacle output 2nd function

**Specified Frequencies Of Discrimination Per Function:** 

1.00 megahertz blank and 5.50 megahertz blank and 88.00 megahertz blank and 1.00 gigahertz blank

**Thread Size:** 

0.500 inches

**Frequency Band Width Per Function:** 

1.00 megahertz blank and 5.50 megahertz blank

## NSN 5915-00-879-0448

Low Pass Filter - Page 2 of 2



<b>Discrimination At Speci</b>	ficationified Frequ	ıencies Per Fu	ınction In Decibels:
--------------------------------	---------------------	----------------	----------------------

3.0 blank and 3.0 blank and 70.0 blank and 80.0 blank

**Style Designator:** 

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0