

View Online at <https://aerobasegroup.com/nsn/5915-00-879-2490>

Body Length:

4.031 inches

Body Width:

1.344 inches

Body Height:

0.969 inches

Unthreaded Mounting Hole Diameter:

0.220 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.500 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Operating Temperature Range:

-10.0/+70.0 degrees celsius

Reference Frequency Per Function:

312.5 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Input Terminal Manufacturer Code:

81349

Input Terminal Identification:

Ug913a/u

Output Terminal Manufacturer Code:

81349

Output Terminal Identification:

Ug88e/u

Voltage Standing Wave Ratio Per Function:

1.3 blank

Average Power Rating Per Function:

60.0 watts blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 wire lead input 1st function

Specified Frequencies Of Discrimination Per Function:

220.00 megahertz blank and 405.00 megahertz blank and 450.00 megahertz blank and 2.00 gigahertz blank

Frequency Band Width Per Function:

220.00 megahertz blank and 405.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 1.0 blank and 35.0 blank and 35.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

220.0 megahertz blank and 405.0 megahertz blank

Special Features:

Wire leads with plug connectors

Unpackaged Unit Weight:

1.000 pounds

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0