

View Online at <https://aerobasegroup.com/nsn/5915-00-884-0854>

Unthreaded Mounting Hole Diameter:

0.125 inches

Reference Frequency Per Function:

1.1 gigahertz blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Voltage Standing Wave Ratio Per Function:

1.5 blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

3 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

0.9 blank

Functional Terminal Type And Quantity:

1 wire lead input 1st function

Specified Frequencies Of Discrimination Per Function:

950.00 megahertz blank and 1.25 gigahertz blank and 1.44 gigahertz blank and 2.88 gigahertz blank

Frequency Band Width Per Function:

950.00 megahertz blank and 1.25 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 3.0 blank and 20.0 blank and 20.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

950.0 megahertz blank and 1.23 gigahertz blank

Special Features:

One wire lead with connector receptacle; one wire lead with pin terminal

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0