NSN 5915-00-884-2046

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-884-2046
Overall Height:
1.750 inches
Body Length:
1.000 inches
Body Width:
1.000 inches
Body Height:
1.375 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.750 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.750 inches
Operating Tempurature Range:
-55.0/+105.0 degrees celsius
Average Life Rating In Hours:
10000.0
Reference Frequency Per Function:
150.0 hertz blank
Source Impedance Rating Per Function:
10.0 kilohms blank
Load Impedance Per Function:
10.0 kilohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
6.0 blank
Functional Terminal Type And Quantity:
1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

0.00 hertz blank and 300.00 hertz blank and 450.00 hertz blank and 600.00 hertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

0.00 hertz blank and 300.00 hertz blank

NSN 5915-00-884-2046

Low Pass Filter - Page 2 of 2



Discrimination At Specificationified Frequencies Per Function In Decibels:

6.0 blank and 6.0 blank and 30.0 blank and 40.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A047b0