## NSN 5915-00-889-4358

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-889-4358

Overall Height:
2.380 inches
Body Length:
3.000 inches
Body Width:
1.620 inches
Body Height:
2.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.120 inches
Operating Tempurature Range:
-20.0/+85.0 degrees celsius
Reference Frequency Per Function:
79.75 kilohertz blank
Source Impedance Rating Per Function:
600.0 ohms blank
Load Impedance Per Function:
600.0 ohms blank
Input Impedance Per Function W/load:
600.0 ohms blank
Output Impedance Per Function W/source Across Input:
600.0 ohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
4 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
0.1 blank
Functional Terminal Type And Quantity:
2 tab, solder lug ground 3rd function
Specified Frequencies Of Discrimination Per Function:
250.00 hertz blank and 80.00 kilohertz blank and 140.00 kilohertz blank and 225.00 kilohertz blank
Thread Size:
0.138 inches
Body Material:
Metal
Frequency Band Width Per Function:

250.00 hertz blank and 80.00 kilohertz blank

## NSN 5915-00-889-4358

Low Pass Filter - Page 2 of 2



## Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 1.0 blank and 40.0 blank and 45.0 blank

**Style Designator:** 

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0