## NSN 5915-00-889-4399

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-889-4399

Overall Height:
2.380 inches
Body Length:
3.000 inches
Body Width:
1.750 inches
Body Height:
2.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.250 inches
Vibration Resistance Range In Hertz:
+10.0/+55.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.125 inches
Operating Tempurature Range:
-20.0/+85.0 degrees celsius
Reference Frequency Per Function:
225.0 kilohertz blank
Input Impedance Per Function W/load:
300.0 ohms blank
Output Impedance Per Function W/source Across Input:
300.0 ohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
4 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
0.5 blank
Functional Terminal Type And Quantity:
2 tab, solder lug ground 3rd function
Specified Frequencies Of Discrimination Per Function:
100.00 kilohertz blank and 350.00 kilohertz blank and 1.50 megahertz blank and 2.00 megahertz blank
Thread Size:
0.138 inches
Body Material:
Metal
Frequency Band Width Per Function:
100.00 kilohertz blank and 350.00 kilohertz blank

2.0 blank and 2.5 blank and 45.0 blank and 45.0 blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

## NSN 5915-00-889-4399

Low Pass Filter - Page 2 of 2



Unpackaged Unit Weight:
1.000 pounds
Style Designator:
Rectangular terminal/terminals on one surface
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A047b0