# NSN 5915-00-889-4399

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-889-4399

# **Overall Height:**

2.380 inches

## **Body Length:**

3.000 inches

# Body Width:

1.750 inches

#### **Body Height:**

## 2.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

#### 2.250 inches

## Vibration Resistance Range In Hertz:

## +10.0/+55.0

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.125 inches

## **Operating Tempurature Range:**

## -20.0/+85.0 degrees celsius

## **Reference Frequency Per Function:**

225.0 kilohertz blank

## Input Impedance Per Function W/load:

300.0 ohms blank

## Output Impedance Per Function W/source Across Input:

300.0 ohms blank

## Mounting Facility Screw Thread Series Designator:

Unc

#### Inclosure Type:

Hermetically sealed

## Mounting Facility Type And Quantity:

4 threaded stud

## Insertion Loss At Reference Frequency Per Function In Decibels:

0.5 blank

## Functional Terminal Type And Quantity:

2 tab, solder lug ground 3rd function

## **Specified Frequencies Of Discrimination Per Function:**

100.00 kilohertz blank and 350.00 kilohertz blank and 1.50 megahertz blank and 2.00 megahertz blank

#### Thread Size:

0.138 inches

#### **Body Material:**

Metal

#### **Frequency Band Width Per Function:**

100.00 kilohertz blank and 350.00 kilohertz blank

#### Discrimination At Specificationified Frequencies Per Function In Decibels:

2.0 blank and 2.5 blank and 45.0 blank and 45.0 blank

# NSN 5915-00-889-4399

Low Pass Filter - Page 2 of 2



# Unpackaged Unit Weight:

1.000 pounds

# Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A047b0