

View Online at <https://aerobasegroup.com/nsn/5915-00-890-7902>

**Overall Height:**

5.000 inches

**Body Length:**

4.312 inches

**Body Width:**

3.687 inches

**Body Height:**

4.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

3.312 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

2.687 inches

**Operating Temperature Range:**

+15.0/+55.0 degrees celsius

**Reference Frequency Per Function:**

400.0 hertz blank

**Input Impedance Per Function W/load:**

400.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

400.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Functional Terminal Type And Quantity:**

1 turret input and 1 turret output and 1 turret ground

**Maximum Dielectric Withstanding Ac Rms Voltage:**

1.5 kilovolts at sea level

**Specified Frequencies Of Discrimination Per Function:**

120.00 hertz blank and 390.00 hertz blank and 410.00 hertz blank and 1.20 kilohertz blank

**Thread Size:**

0.190 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

390.00 hertz blank and 410.00 hertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

20.0 blank and 3.0 blank and 3.0 blank and 20.0 blank

**Unpackaged Unit Weight:**

3.000 pounds

**Style Designator:**

Rectangular terminal/terminals on one surface

**Test Data Document:**

03538-7644939 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A047b0