## NSN 5915-00-891-2356

Band Pass Filter - Page 1 of 2



equipment manufacturer drawing, etc.;

View Online at https://aerobasegroup.com/nsn/5915-00-891-2356

Overall H	leight:
1.320 inc	hes
Body Lei	ngth:
Between	1.740 inches and 1.760 inches
Body Wi	dth:
Between	1.240 inches and 1.260 inches
Body He	ight:
Between	1.050 inches and 1.070 inches
Distance	Between Centerlines Of Mounting Facilities Parallel To Body Length:
Between	1.240 inches and 1.260 inches
Reference	e Frequency Per Function:
2.0 mega	hertz blank
Input Imp	pedance Per Function W/load:
1.0 kilohn	ns blank
Output Ir	npedance Per Function W/source Across Input:
1.0 kilohn	ns blank
Mounting	g Facility Screw Thread Series Designator:
Unc	
Inclosure	э Туре:
Hermetica	ally sealed
Mounting	g Facility Type And Quantity:
2 threade	d stud
Insertion	Loss At Reference Frequency Per Function In Decibels:
6.0 blank	
Function	al Terminal Type And Quantity:
1 pin outp	put 2nd function
Specified	I Frequencies Of Discrimination Per Function:
1.998 me	gahertz blank and 1.9995 megahertz blank and 2.0005 megahertz blank and 2.002 megahertz blank
Thread S	ize:
0.112 inc	hes
Frequence	cy Band Width Per Function:
1.9995 m	egahertz blank and 2.0005 megahertz blank
Discrimi	nation At Specificationified Frequencies Per Function In Decibels:
40.0 blar	ik and 3.0 blank and 3.0 blank and 40.0 blank
Style Des	signator:
Rectangu	lar terminal/terminals on one surface
Test Data	a Document:
14632-20	811 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment m
excludes	any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life	
N/a	
Unit Of M	leasure:

## NSN 5915-00-891-2356

Band Pass Filter - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A047b0

