

View Online at <https://aerobasegroup.com/nsn/5915-00-891-2357>

**Overall Height:**

Between 1.240 inches and 1.260 inches

**Body Length:**

Between 2.430 inches and 2.450 inches

**Body Width:**

Between 1.590 inches and 1.610 inches

**Body Height:**

Between 0.990 inches and 1.010 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 1.970 inches and 1.990 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.050 inches and 1.070 inches

**Operating Temperature Range:**

+0.0/+50.0 degrees celsius

**Reference Frequency Per Function:**

2.0 megahertz blank

**Input Impedance Per Function W/load:**

1.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

1.0 kilohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

6.0 blank

**Functional Terminal Type And Quantity:**

1 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

1.9975 megahertz blank and 1.9985 megahertz blank and 2.0015 megahertz blank and 2.0025 megahertz blank

**Thread Size:**

0.112 inches

**Frequency Band Width Per Function:**

1.9985 megahertz blank and 2.0015 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

40.0 blank and 3.0 blank and 3.0 blank and 40.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Test Data Document:**

14632-20812 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0