

View Online at <https://aerobasegroup.com/nsn/5915-00-891-2357>

Overall Height:

Between 1.240 inches and 1.260 inches

Body Length:

Between 2.430 inches and 2.450 inches

Body Width:

Between 1.590 inches and 1.610 inches

Body Height:

Between 0.990 inches and 1.010 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.970 inches and 1.990 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.050 inches and 1.070 inches

Operating Temperature Range:

+0.0/+50.0 degrees celsius

Reference Frequency Per Function:

2.0 megahertz blank

Input Impedance Per Function W/load:

1.0 kilohms blank

Output Impedance Per Function W/source Across Input:

1.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.9975 megahertz blank and 1.9985 megahertz blank and 2.0015 megahertz blank and 2.0025 megahertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

1.9985 megahertz blank and 2.0015 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

40.0 blank and 3.0 blank and 3.0 blank and 40.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

14632-20812 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0