

View Online at <https://aerobasegroup.com/nsn/5915-00-899-0710>

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

15.375 inches

Reference Frequency Per Function:

425.0 megahertz blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Voltage Standing Wave Ratio Per Function:

2.0 blank

Average Power Rating Per Function:

5.0 kilowatts blank

Inclosure Type:

Uninclosed

Mounting Facility Type And Quantity:

2 flange

Cubic Measure:

179.0 cubic inches

Insertion Loss At Reference Frequency Per Function In Decibels:

0.25 blank

Functional Terminal Type And Quantity:

1 circular flange output 2nd function

Specified Frequencies Of Discrimination Per Function:

400.00 megahertz blank and 450.00 megahertz blank and 800.00 megahertz blank and 2.25 gigahertz blank

Frequency Band Width Per Function:

400.00 megahertz blank and 450.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 1.0 blank and 27.0 blank and 20.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

400.0 megahertz blank and 450.0 megahertz blank

Unpackaged Unit Weight:

2.500 pounds

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0