NSN 5915-00-899-1720

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-899-1720

Overall Height:

Between 2.876 inches and 3.187 inches

Body Length:

Between 1.812 inches and 1.937 inches

Body Width:

Between 1.687 inches and 1.812 inches

Body Height:

Between 2.563 inches and 2.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.374 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

Operating Tempurature Range:

-55.0/+85.0 degrees celsius

Reference Frequency Per Function:

1.85 kilohertz blank

Source Impedance Rating Per Function:

600.0 ohms blank

Load Impedance Per Function:

600.0 ohms blank

Input Impedance Per Function W/load:

600.0 ohms blank

Output Impedance Per Function W/source Across Input:

600.0 ohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

1.2 blank

Functional Terminal Type And Quantity:

2 turret input 1st function

Specified Frequencies Of Discrimination Per Function:

400.00 hertz blank and 2.00 kilohertz blank and 2.80 kilohertz blank and 3.50 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

400.00 hertz blank and 2.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.2 blank and 1.2 blank and 50.0 blank and 50.0 blank

NSN 5915-00-899-1720

Low Pass Filter - Page 2 of 2



Style Designator:
Rectangular terminal/te

erminals on one surface

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0