

View Online at <https://aerobasegroup.com/nsn/5915-00-902-5572>

Overall Height:

0.688 inches

Body Length:

Between 1.245 inches and 1.255 inches

Body Width:

Between 0.745 inches and 0.755 inches

Body Height:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.531 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-40.0/+65.0 degrees celsius

Reference Frequency Per Function:

500.0 kilohertz blank

Source Impedance Rating Per Function:

20.0 kilohms blank

Load Impedance Per Function:

50.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

2 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

400.00 kilohertz blank and 487.50 kilohertz blank and 512.50 kilohertz blank and 600.00 kilohertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

487.50 kilohertz blank and 512.50 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

55.0 blank and 1.0 blank and 1.0 blank and 45.0 blank

Body Surface Treatment:

Gold

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0