NSN 5915-00-904-7050

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-904-7050

| Overall Height: | | | | | | |
|--|--|--|--|--|--|--|
| 3.360 inches | | | | | | |
| Body Length: | | | | | | |
| 4.500 inches | | | | | | |
| Body Width: | | | | | | |
| 1.530 inches | | | | | | |
| Body Height: | | | | | | |
| 3.000 inches | | | | | | |
| Unthreaded Mounting Hole Diameter: | | | | | | |
| 0.160 inches | | | | | | |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: | | | | | | |
| 3.750 inches | | | | | | |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: | | | | | | |
| 1.562 inches | | | | | | |
| Operating Tempurature Range: | | | | | | |
| -40.0/+75.0 degrees celsius | | | | | | |
| Average Life Rating In Hours: | | | | | | |
| 10000.0 | | | | | | |
| Reference Frequency Per Function: | | | | | | |
| 76.0 single radio interference two phase to two phase | | | | | | |
| Source Impedance Rating Per Function: | | | | | | |
| 600.0 ohms 2nd band pass | | | | | | |
| Load Impedance Per Function: | | | | | | |

2.0 kilohms 2nd band pass

Input Impedance Per Function W/load:

600.0 ohms 1st band pass600.0 ohms 2nd band pass

Output Impedance Per Function W/source Across Input:

2.0 kilohms 1st band pass2.0 kilohms 2nd band pass

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 pin input 1st function1 pin output 2nd function2 pin ground 3rd function

Unpackaged Unit Weight:

1.300 pounds

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

NSN 5915-00-904-7050

Band Pass Filter - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A047b0