

View Online at https://aerobasegroup.com/nsn/5915-00-905-1008

Overall Length: 4.452 inches Body Length: 3.406 inches Body Outside Diameter: 1.250 inches Vibration Resistance Range In Hertz: +10.0/+55.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function:
Body Length: 3.406 inches Body Outside Diameter: 1.250 inches Vibration Resistance Range In Hertz: +10.0/+55.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank
3.406 inches Body Outside Diameter: 1.250 inches Vibration Resistance Range In Hertz: +10.0/+55.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank
Body Outside Diameter: 1.250 inches Vibration Resistance Range In Hertz: +10.0/+55.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank
1.250 inches Vibration Resistance Range In Hertz: +10.0/+55.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank
Vibration Resistance Range In Hertz: +10.0/+55.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank
+10.0/+55.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank
Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank
-55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank
Source Impedance Rating Per Function: 50.0 ohms blank
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Power Line Frequency Rating Per Function In Hertz:
400.0 blank
Operating Current Rating Per Function In Amps:
10.0 blank
Maximum Voltage Drop Per Function:
0.3 volts dc blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Maximum Tempurature Rise:
25.0 degrees celsius
Mounting Facility Screw Thread Series Designator:
Unef
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
1 threaded bushing
Features Provided:
Nut and washer
Functional Terminal Type And Quantity:
1 tab, solder lug output 2nd function
Operating Voltage Rating And Type Per Function:
125.0 volts ac blank and 400.0 volts dc blank
Thread Size:
0.625 inches
Body Material:
Metal
Maximum Dielectric Withstanding Dc Voltage:
250.0 volts at sea level



Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A047b0