

View Online at <https://aerobasegroup.com/nsn/5915-00-905-6860>

Overall Height:

0.793 inches

Body Length:

0.725 inches

Body Width:

0.585 inches

Body Height:

0.765 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 0.555 inches and 0.565 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.415 inches and 0.425 inches

Operating Temperature Range:

-28.0/+65.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

23.5 megahertz blank

Input Impedance Per Function W/load:

1.6 kilohms blank

Output Impedance Per Function W/source Across Input:

1.6 kilohms blank

Principal Circuitry Type Per Function:

Crystal blank

Inclosure Type:

Hermetically sealed

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

2 wire lead output 2nd function

Specified Frequencies Of Discrimination Per Function:

23.43 megahertz blank and 23.46 megahertz blank and 23.54 megahertz blank and 23.57 megahertz blank

Frequency Band Width Per Function:

23.46 megahertz blank and 23.54 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 6.0 blank and 6.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

27914-697354-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0