

View Online at <https://aerobasegroup.com/nsn/5915-00-905-6860>

**Overall Height:**

0.793 inches

**Body Length:**

0.725 inches

**Body Width:**

0.585 inches

**Body Height:**

0.765 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 0.555 inches and 0.565 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.415 inches and 0.425 inches

**Operating Temperature Range:**

-28.0/+65.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

23.5 megahertz blank

**Input Impedance Per Function W/load:**

1.6 kilohms blank

**Output Impedance Per Function W/source Across Input:**

1.6 kilohms blank

**Principal Circuitry Type Per Function:**

Crystal blank

**Inclosure Type:**

Hermetically sealed

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Functional Terminal Type And Quantity:**

2 wire lead output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

23.43 megahertz blank and 23.46 megahertz blank and 23.54 megahertz blank and 23.57 megahertz blank

**Frequency Band Width Per Function:**

23.46 megahertz blank and 23.54 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

60.0 blank and 6.0 blank and 6.0 blank and 60.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Test Data Document:**

27914-697354-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0