

View Online at <https://aerobasegroup.com/nsn/5915-00-905-7404>

Overall Length:

3.594 inches

Body Length:

Between 1.938 inches and 2.062 inches

Body Width:

Between 0.813 inches and 0.937 inches

Body Height:

Between 1.938 inches and 2.062 inches

Unthreaded Mounting Hole Diameter:

0.187 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.375 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Average Life Rating In Hours:

250.0

Operating Current Rating Per Function In Amps:

3.0 blank and 3.0 blank

Maximum Voltage Drop Per Function:

5.0 volts screw on tube not specified and 5.0 volts 23rd band suppression not specified

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Maximum Temperature Rise:

25.0 degrees celsius

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 unthreaded hole

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Operating Voltage Rating And Type Per Function:

125.0 volts ac blank and 400.0 volts dc blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Test Data Document:

81349-milf15733-4c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0