NSN 5915-00-905-7416

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-905-7416

Body Length:
1.000 inches
Body Width:
1.000 inches
Body Height:
1.375 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.750 inches
Reference Frequency Per Function:
1.5 kilohertz blank
Source Impedance Rating Per Function:
10.0 kilohms blank
Load Impedance Per Function:
10.0 kilohms blank
Input Impedance Per Function W/load:
10.0 kilohms blank
Output Impedance Per Function W/source Across Input:
10.0 kilohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
4 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
0.0 blank
Specified Frequencies Of Discrimination Per Function:
0.00 kilohertz blank and 3.00 kilohertz blank and 4.50 kilohertz blank and 4.50 kilohertz blank
Thread Size:
0.138 inches
Frequency Band Width Per Function:
0.00 kilohertz blank and 3.00 kilohertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:
6.0 blank and 6.0 blank and 30.0 blank and 30.0 blank
Style Designator:
Rectangular terminal/terminals on one surface
Shelf Life:
N/a
Unit Of Measure:

NSN 5915-00-905-7416

Low Pass Filter - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A047b0