## NSN 5915-00-910-7123

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-910-7123

| Overall Height:   |
|---|
| 0.985 inches  |
| Body Length:  |
| 2.734 inches  |
| Body Width:   |
| 0.500 inches  |
| Body Height:  |
| 0.766 inches  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:                            |
| Between 1.492 inches and 1.508 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:                             |
| Between 0.192 inches and 0.208 inches   |
| Operating Tempurature Range:  |
| -40.0/+75.0 degrees celsius   |
| Reference Frequency Per Function:   |
| 455.0 kilohertz blank   |
| Source Impedance Rating Per Function:   |
| 50.0 kilohms blank  |
| Load Impedance Per Function:  |
| 500.0 ohms blank  |
| Principal Circuitry Type Per Function:  |
| Inductance-capacitance blank  |
| Mounting Facility Screw Thread Series Designator:   |
| Unc   |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Type And Quantity:  |
| 2 threaded stud   |
| Insertion Loss At Reference Frequency Per Function In Decibels:   |
| 10.5 blank  |
| Functional Terminal Type And Quantity:  |
| 2 pin ground 3rd function   |
| Specified Frequencies Of Discrimination Per Function:   |
| 454.55 megahertz blank and 454.73 megahertz blank and 455.27 megahertz blank and 455.45 megahertz blank |
| Thread Size:  |
| 0.112 inches  |
| Body Material:  |
| Metal   |
| Frequency Band Width Per Function:  |
| 454.55 megahertz blank and 455.45 megahertz blank   |

70.0 blank and 3.5 blank and 3.5 blank and 70.0 blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

## NSN 5915-00-910-7123

Band Pass Filter - Page 2 of 2



| Style Designator:  |
|--------------------|
| Rectangular termin |

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0