

View Online at <https://aerobasegroup.com/nsn/5915-00-910-7145>

**Overall Height:**

Between 2.890 inches and 3.010 inches

**Body Length:**

Between 5.670 inches and 5.730 inches

**Body Width:**

Between 3.140 inches and 3.200 inches

**Body Height:**

Between 2.420 inches and 2.480 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 4.970 inches and 5.030 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 2.460 inches and 2.520 inches

**Reference Frequency Per Function:**

102.9375 kilohertz blank

**Source Impedance Rating Per Function:**

750.0 ohms blank

**Load Impedance Per Function:**

750.0 ohms blank

**Input Impedance Per Function W/load:**

750.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

750.0 ohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

1.0 blank

**Functional Terminal Type And Quantity:**

2 tab, solder lug output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

99.80 kilohertz blank and 100.12 kilohertz blank and 106.00 kilohertz blank and 106.07 kilohertz blank

**Thread Size:**

0.164 inches

**Frequency Band Width Per Function:**

100.12 kilohertz blank and 106.00 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

60.0 blank and 1.0 blank and 1.0 blank and 60.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0