

View Online at <https://aerobasegroup.com/nsn/5915-00-910-7145>

Overall Height:

Between 2.890 inches and 3.010 inches

Body Length:

Between 5.670 inches and 5.730 inches

Body Width:

Between 3.140 inches and 3.200 inches

Body Height:

Between 2.420 inches and 2.480 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 4.970 inches and 5.030 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.460 inches and 2.520 inches

Reference Frequency Per Function:

102.9375 kilohertz blank

Source Impedance Rating Per Function:

750.0 ohms blank

Load Impedance Per Function:

750.0 ohms blank

Input Impedance Per Function W/load:

750.0 ohms blank

Output Impedance Per Function W/source Across Input:

750.0 ohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

2 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

99.80 kilohertz blank and 100.12 kilohertz blank and 106.00 kilohertz blank and 106.07 kilohertz blank

Thread Size:

0.164 inches

Frequency Band Width Per Function:

100.12 kilohertz blank and 106.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 1.0 blank and 1.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0