

View Online at <https://aerobasegroup.com/nsn/5915-00-914-5341>

Overall Height:

Between 1.118 inches and 1.182 inches

Body Length:

Between 2.234 inches and 2.266 inches

Body Width:

Between 0.980 inches and 1.020 inches

Body Height:

Between 0.784 inches and 0.816 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.585 inches and 1.695 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.595 inches and 0.605 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

5.1250 megahertz blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Principal Circuitry Type Per Function:

Crystal blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

0.0 blank

Functional Terminal Type And Quantity:

1 solder stud input 1st function

Specified Frequencies Of Discrimination Per Function:

4.995 megahertz blank and 5.083 megahertz blank and 5.167 megahertz blank and 5.255 megahertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

5.083 megahertz blank and 5.167 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

80.0 blank and 6.0 blank and 6.0 blank and 80.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0