NSN 5915-00-916-5968

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-916-5968

Overall Height:
0.984 inches
Body Length:
3.750 inches
Body Width:
3.500 inches
Body Height:
0.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
3.125 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.875 inches
Operating Tempurature Range:
-30.0/+65.0 degrees celsius
Reference Frequency Per Function:
118.0 kilohertz blank
Input Impedance Per Function W/load:
51.0 ohms blank
Output Impedance Per Function W/source Across Input:
51.0 ohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
4 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
1.0 blank
Functional Terminal Type And Quantity:
2 pin ground 3rd function
Maximum Dielectric Withstanding Ac Rms Voltage:
500.0 volts at sea level
Specified Frequencies Of Discrimination Per Function:
1.00 kilohertz blank and 235.00 kilohertz blank and 680.00 kilohertz blank and 944.00 kilohertz blank
Thread Size:
0.164 inches
Body Material:
Metal
Frequency Band Width Per Function:
1.00 kilohertz blank and 235.00 kilohertz blank

3.0 blank and 3.0 blank and 24.0 blank and 39.0 blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

NSN 5915-00-916-5968

Low Pass Filter - Page 2 of 2



Style	De	sia	nato	١r٠
OLYIC	De.	oig:	IIau	<i>,</i> ,

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A047b0