

View Online at <https://aerobasegroup.com/nsn/5915-00-918-7881>

Overall Height:

4.880 inches

Body Length:

2.000 inches

Body Width:

1.500 inches

Body Height:

4.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.438 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.938 inches

Operating Temperature Range:

-55.0/+65.0 degrees celsius

Average Life Rating In Hours:

1000.0

Reference Frequency Per Function:

1.8 kilohertz blank

Source Impedance Rating Per Function:

1.0 kilohms blank

Load Impedance Per Function:

600.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

2.0 blank

Functional Terminal Type And Quantity:

2 pin output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

450.00 hertz blank and 1.20 kilohertz blank and 2.40 kilohertz blank and 5.15 kilohertz blank

Thread Size:

0.164 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.20 kilohertz blank and 2.40 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

6.0 blank and 2.0 blank and 2.0 blank and 6.0 blank

Body Surface Treatment:

Tin

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0