

View Online at <https://aerobasegroup.com/nsn/5915-00-918-7881>

**Overall Height:**

4.880 inches

**Body Length:**

2.000 inches

**Body Width:**

1.500 inches

**Body Height:**

4.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.438 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.938 inches

**Operating Temperature Range:**

-55.0/+65.0 degrees celsius

**Average Life Rating In Hours:**

1000.0

**Reference Frequency Per Function:**

1.8 kilohertz blank

**Source Impedance Rating Per Function:**

1.0 kilohms blank

**Load Impedance Per Function:**

600.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

2.0 blank

**Functional Terminal Type And Quantity:**

2 pin output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

500.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

450.00 hertz blank and 1.20 kilohertz blank and 2.40 kilohertz blank and 5.15 kilohertz blank

**Thread Size:**

0.164 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.20 kilohertz blank and 2.40 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

6.0 blank and 2.0 blank and 2.0 blank and 6.0 blank

**Body Surface Treatment:**

Tin

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0