## NSN 5915-00-918-7922

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-918-7922

Overall Height:
6.120 inches
Body Length:
3.000 inches
Body Width:
1.500 inches
Body Height:
5.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.438 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.938 inches
Reference Frequency Per Function:
680.0 hertz blank
Input Impedance Per Function W/load:
600.0 ohms blank
Output Impedance Per Function W/source Across Input:
5.0 kilohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
4 threaded stud
4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels:
Insertion Loss At Reference Frequency Per Function In Decibels:
Insertion Loss At Reference Frequency Per Function In Decibels: 2.0 blank
Insertion Loss At Reference Frequency Per Function In Decibels: 2.0 blank Functional Terminal Type And Quantity:
Insertion Loss At Reference Frequency Per Function In Decibels: 2.0 blank  Functional Terminal Type And Quantity: 3 pin output 2nd function
Insertion Loss At Reference Frequency Per Function In Decibels: 2.0 blank Functional Terminal Type And Quantity: 3 pin output 2nd function Specified Frequencies Of Discrimination Per Function:
Insertion Loss At Reference Frequency Per Function In Decibels:  2.0 blank  Functional Terminal Type And Quantity:  3 pin output 2nd function  Specified Frequencies Of Discrimination Per Function:  295.00 hertz blank and 510.00 hertz blank and 850.00 hertz blank and 1.06 kilohertz blank
Insertion Loss At Reference Frequency Per Function In Decibels:  2.0 blank  Functional Terminal Type And Quantity:  3 pin output 2nd function  Specified Frequencies Of Discrimination Per Function:  295.00 hertz blank and 510.00 hertz blank and 850.00 hertz blank and 1.06 kilohertz blank  Thread Size:
Insertion Loss At Reference Frequency Per Function In Decibels:  2.0 blank  Functional Terminal Type And Quantity:  3 pin output 2nd function  Specified Frequencies Of Discrimination Per Function:  295.00 hertz blank and 510.00 hertz blank and 850.00 hertz blank and 1.06 kilohertz blank  Thread Size:  0.164 inches
Insertion Loss At Reference Frequency Per Function In Decibels:  2.0 blank  Functional Terminal Type And Quantity:  3 pin output 2nd function  Specified Frequencies Of Discrimination Per Function:  295.00 hertz blank and 510.00 hertz blank and 850.00 hertz blank and 1.06 kilohertz blank  Thread Size:  0.164 inches  Body Material:
Insertion Loss At Reference Frequency Per Function In Decibels:  2.0 blank  Functional Terminal Type And Quantity:  3 pin output 2nd function  Specified Frequencies Of Discrimination Per Function:  295.00 hertz blank and 510.00 hertz blank and 850.00 hertz blank and 1.06 kilohertz blank  Thread Size:  0.164 inches  Body Material:  Metal
Insertion Loss At Reference Frequency Per Function In Decibels:  2.0 blank  Functional Terminal Type And Quantity:  3 pin output 2nd function  Specified Frequencies Of Discrimination Per Function:  295.00 hertz blank and 510.00 hertz blank and 850.00 hertz blank and 1.06 kilohertz blank  Thread Size:  0.164 inches  Body Material:  Metal  Frequency Band Width Per Function:
Insertion Loss At Reference Frequency Per Function In Decibels:  2.0 blank  Functional Terminal Type And Quantity:  3 pin output 2nd function  Specified Frequencies Of Discrimination Per Function:  295.00 hertz blank and 510.00 hertz blank and 850.00 hertz blank and 1.06 kilohertz blank  Thread Size:  0.164 inches  Body Material:  Metal  Frequency Band Width Per Function:  510.00 hertz blank and 850.00 hertz blank

N/a

Shelf Life:

Rectangular terminal/terminals on one surface

## NSN 5915-00-918-7922

Band Pass Filter - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A047b0