

View Online at <https://aerobasegroup.com/nsn/5915-00-921-0361>

**Overall Length:**

Between 2.889 inches and 2.983 inches

**Body Length:**

Between 1.969 inches and 2.031 inches

**Body Width:**

Between 1.094 inches and 1.156 inches

**Body Height:**

Between 1.969 inches and 2.031 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.182 inches and 0.192 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 2.359 inches and 2.391 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Average Life Rating In Hours:**

250.0

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Power Line Frequency Rating Per Function In Hertz:**

400.0 blank

**Operating Current Rating Per Function In Amps:**

10.0 blank

**Maximum Voltage Drop Per Function:**

1.25 volts ac blank and 1.25 volts dc blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Maximum Temperature Rise:**

25.0 degrees celsius

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Functional Terminal Type And Quantity:**

1 threaded stud output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

500.0 volts at sea level

**Functional Terminal Thread Diameter:**

0.164 inches input-output

**Operating Voltage Rating And Type Per Function:**

125.0 volts ac blank and 400.0 volts dc blank

**Functional Terminal Thread Quantity:**

32.0 per inch input-output

**Maximum Dielectric Withstanding Dc Voltage:**

500.0 volts at sea level

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Test Data Document:**

81349-milf15733-16a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0