

View Online at <https://aerobasegroup.com/nsn/5915-00-921-4502>

**Overall Height:**

3.230 inches

**Body Length:**

3.000 inches

**Body Width:**

1.410 inches

**Body Height:**

2.950 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Operating Temperature Range:**

-55.0/+65.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

425.0 single high pass two phase to two phase

**Source Impedance Rating Per Function:**

600.0 ohms 3rd band pass

**Load Impedance Per Function:**

600.0 ohms 3rd band pass

**Principal Circuitry Type Per Function:**

Inductance-capacitance 3rd band pass 3rd function

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded hole

**Features Provided:**

Electrostatic shield

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 2nd band pass

**Functional Terminal Type And Quantity:**

3 turret output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

382.50 hertz 3rd band pass 3rd function and 403.75 hertz 3rd band pass 3rd function and 446.25 hertz 3rd band pass 3rd function and 467.50 hertz 3rd band pass 3rd function

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

403.75 hertz 3rd band pass and 446.25 hertz 3rd band pass

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 3rd band pass 3rd function and 30.0 3rd band pass 3rd function

**Maximum Dielectric Withstanding Dc Voltage:**

500.0 volts at sea level

**Special Features:**

Electrostatic shield brought out to terminal six

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0