

View Online at <https://aerobasegroup.com/nsn/5915-00-921-4513>

Overall Height:

3.230 inches

Body Length:

3.000 inches

Body Width:

1.410 inches

Body Height:

2.950 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-55.0/+65.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

2.125 single radio interference two phase to two phase

Source Impedance Rating Per Function:

600.0 ohms 3rd band pass

Load Impedance Per Function:

600.0 ohms 3rd band pass

Principal Circuitry Type Per Function:

Inductance-capacitance 3rd band pass 3rd function

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded hole

Features Provided:

Electrostatic shield

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 2nd band pass

Functional Terminal Type And Quantity:

3 turret output 2nd function

Specified Frequencies Of Discrimination Per Function:

2.0825 kilohertz 3rd band pass 3rd function and 2.10375 kilohertz 3rd band pass 3rd function and 2.14625 kilohertz 3rd band pass 3rd function and 2.1675 kilohertz 3rd band pass 3rd function

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

2.10375 kilohertz 1st band pass and 2.14625 kilohertz 1st band pass

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 3rd band pass 3rd function and 30.0 3rd band pass 3rd function

Maximum Dielectric Withstanding Dc Voltage:

500.0 volts at sea level

Special Features:

Electrostatic shield brought out to terminal six

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0