

View Online at <https://aerobasegroup.com/nsn/5915-00-921-5791>

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference 50.0 ohms 3rd radio interference 50.0 ohms 4th radio interference 50.0 ohms 5th radio interference 50.0 ohms 6th radio interference

**Load Impedance Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference 50.0 ohms 3rd radio interference 50.0 ohms 4th radio interference 50.0 ohms 5th radio interference 50.0 ohms 6th radio interference

**Power Line Frequency Rating Per Function In Hertz:**

60.0 1st radio interference 60.0 2nd radio interference 60.0 3rd radio interference 60.0 4th radio interference 60.0 5th radio interference 60.0 6th radio interference

**Operating Current Rating Per Function In Amps:**

3.0 1st radio interference 3.0 2nd radio interference 3.0 3rd radio interference 3.0 4th radio interference 3.0 5th radio interference 3.0 6th radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference inductance-capacitance 3rd radio interference inductance-capacitance 4th radio interference inductance-capacitance 5th radio interference inductance-capacitance 6th radio interference

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

3 slot

**Functional Terminal Type And Quantity:**

1 connector, receptacle input 1st function 12 tab, solder lug output 2nd function 2 wire lead ground 3rd function

**Operating Voltage Rating And Type Per Function:**

120.0 volts ac 1st radio interference 1st function 120.0 volts ac 2nd radio interference 2nd function 120.0 volts ac 3rd radio interference 3rd function 120.0 volts ac 4th radio interference 4th function 120.0 volts ac 5th radio interference 5th function 120.0 volts ac 6th radio interference 6th function

**Body Material:**

Metal

**Special Features:**

Twelve filtered functions

**Style Designator:**

Rectangular terminal/terminals on two surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0