# NSN 5915-00-921-6026

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-921-6026

# Overall Height:

3.525 inches

## **Body Length:**

4.980 inches

## Body Width:

1.410 inches

## **Body Height:**

## 3.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

#### 4.375 inches

# Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.938 inches

#### **Operating Tempurature Range:**

+0.0/+60.0 degrees celsius

#### **Reference Frequency Per Function:**

## 2.295 single radio interference pulses per second2.295 single radio interference two phase to two phase

# Source Impedance Rating Per Function:

600.0 ohms 2nd band pass

#### Load Impedance Per Function:

600.0 ohms 2nd band pass

# Principal Circuitry Type Per Function:

Inductance-capacitance 2nd band pass 2nd function

# Mounting Facility Screw Thread Series Designator:

Unc

#### Inclosure Type:

Hermetically sealed

#### Mounting Facility Type And Quantity:

4 threaded hole

# Insertion Loss At Reference Frequency Per Function In Decibels:

2.5 2nd band pass

# Functional Terminal Type And Quantity:

1 component socket input-output/ground

# Specified Frequencies Of Discrimination Per Function:

2.17 kilohertz 2nd band pass 2nd function and 2.2525 kilohertz 2nd band pass 2nd function and 2.3375 kilohertz 2nd band pass 2nd function and 2.42 kilohertz 2nd band pass 2nd function

#### Thread Size:

0.138 inches

#### **Body Material:**

Metal

#### Frequency Band Width Per Function:

2.2525 kilohertz 2nd band pass and 2.3375 kilohertz 2nd band pass

#### Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 2nd band pass 2nd function and 45.0 2nd band pass 2nd function

# NSN 5915-00-921-6026

Band Pass Filter - Page 2 of 2



## **Special Features:**

Two filtered functions

## Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

Fiig:

A047b0