## NSN 5915-00-925-1883



Low Pass Filter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5915-00-925-1883 **Overall Length:** 5.312 inches **Overall Height:** 1.562 inches **Body Width:** 2.625 inches **Unthreaded Mounting Hole Diameter:** 0.171 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 4.188 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.875 inches **Operating Tempurature Range:** -55.0/+85.0 degrees celsius **Reference Frequency Per Function:** 2.54 kilohertz blank **Source Impedance Rating Per Function:** 50.0 ohms blank **Load Impedance Per Function:** 50.0 ohms blank **Inclosure Type:** Encased **Mounting Facility Type And Quantity:** 4 unthreaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 1.5 blank **Functional Terminal Type And Quantity:** 2 turret input 1st function **Specified Frequencies Of Discrimination Per Function:** 80.00 hertz blank and 5.00 kilohertz blank and 100.00 kilohertz blank and 32.00 megahertz blank **Frequency Band Width Per Function:** 

80.00 hertz blank and 5.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.5 blank and 1.5 blank and 50.0 blank and 50.0 blank

**Maximum Dielectric Withstanding Dc Voltage:** 

250.0 volts at sea level

**Style Designator:** 

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5915-00-925-1883

Low Pass Filter - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A047b0