

View Online at <https://aerobasegroup.com/nsn/5915-00-927-8657>

**Overall Height:**

1.225 inches

**Body Length:**

4.055 inches

**Body Width:**

1.310 inches

**Body Height:**

1.025 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

3.400 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.900 inches

**Operating Temperature Range:**

-55.0/+105.0 degrees celsius

**Reference Frequency Per Function:**

18.75 kilohertz blank

**Input Impedance Per Function W/load:**

27.99 kilohms blank

**Output Impedance Per Function W/source Across Input:**

27.99 kilohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Functional Terminal Type And Quantity:**

2 wire lead ground 3rd function

**Specified Frequencies Of Discrimination Per Function:**

18.625 kilohertz blank and 18.74 kilohertz blank and 18.76 kilohertz blank and 18.875 kilohertz blank

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

18.74 kilohertz blank and 18.76 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

60.0 blank and 6.0 blank and 6.0 blank and 60.0 blank

**Maximum Dielectric Withstanding Dc Voltage:**

500.0 volts at sea level

**Body Surface Treatment:**

Tin

**Unpackaged Unit Weight:**

284.000 grams

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0