

View Online at <https://aerobasegroup.com/nsn/5915-00-930-4438>

Overall Height:

4.690 inches

Body Length:

3.062 inches

Body Width:

2.625 inches

Body Height:

4.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.281 inches and 2.301 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.610 inches and 2.640 inches

Operating Temperature Range:

-40.0/+80.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

425.0 single high pass two phase to two phase

Source Impedance Rating Per Function:

6.2 kilohms 2nd band pass

Load Impedance Per Function:

180.0 ohms 2nd band pass

Principal Circuitry Type Per Function:

Inductance-capacitance 2nd band pass 2nd function

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

14.0 1st band pass

Functional Terminal Type And Quantity:

2 turret input 1st function

Maximum Dielectric Withstanding Ac Rms Voltage:

150.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

220.00 hertz 2nd band pass 2nd function and 382.50 hertz 2nd band pass 2nd function and 457.50 hertz 2nd band pass 2nd function and 740.00 hertz 2nd band pass 2nd function

Thread Size:

0.164 inches

Body Material:

Metal

Frequency Band Width Per Function:

2.76 kilohertz blank and 2.84 kilohertz blank and 382.50 hertz blank and 457.50 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

16.0 2nd band pass 2nd function and 1.0 2nd band pass 2nd function and 1.0 2nd band pass 2nd function and 16.0 2nd band pass 2nd function

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0