

View Online at <https://aerobasegroup.com/nsn/5915-00-930-4438>

**Overall Height:**

4.690 inches

**Body Length:**

3.062 inches

**Body Width:**

2.625 inches

**Body Height:**

4.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 2.281 inches and 2.301 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 2.610 inches and 2.640 inches

**Operating Temperature Range:**

-40.0/+80.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

425.0 single high pass two phase to two phase

**Source Impedance Rating Per Function:**

6.2 kilohms 2nd band pass

**Load Impedance Per Function:**

180.0 ohms 2nd band pass

**Principal Circuitry Type Per Function:**

Inductance-capacitance 2nd band pass 2nd function

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

14.0 1st band pass

**Functional Terminal Type And Quantity:**

2 turret input 1st function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

150.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

220.00 hertz 2nd band pass 2nd function and 382.50 hertz 2nd band pass 2nd function and 457.50 hertz 2nd band pass 2nd function and 740.00 hertz 2nd band pass 2nd function

**Thread Size:**

0.164 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

2.76 kilohertz blank and 2.84 kilohertz blank and 382.50 hertz blank and 457.50 hertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

16.0 2nd band pass 2nd function and 1.0 2nd band pass 2nd function and 1.0 2nd band pass 2nd function and 16.0 2nd band pass 2nd function

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0