

View Online at <https://aerobasegroup.com/nsn/5915-00-930-4439>

Overall Height:

3.565 inches

Body Length:

2.312 inches

Body Width:

2.062 inches

Body Height:

3.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.687 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.437 inches

Operating Temperature Range:

-40.0/+80.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

2.0 kilohertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance-resistance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

18.0 blank

Functional Terminal Type And Quantity:

1 turret output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

100.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

400.00 hertz blank and 1.25 kilohertz blank and 2.61 kilohertz blank and 3.70 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

1.25 kilohertz blank and 2.61 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

30.0 blank and 3.0 blank and 3.0 blank and 30.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0