NSN 5915-00-930-4440

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-930-4440 **Overall Height:** 4.690 inches **Body Length:** 3.062 inches **Body Width:** 2.625 inches **Body Height:** 4.250 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 2.296 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.859 inches **Operating Tempurature Range:** -40.0/+80.0 degrees celsius **Average Life Rating In Hours:** 10000.0 **Reference Frequency Per Function:** 425.0 single high pass two phase to two phase Input Impedance Per Function W/load: 600.0 ohms 2nd band pass **Output Impedance Per Function W/source Across Input:** 600.0 ohms 2nd band pass **Mounting Facility Screw Thread Series Designator:** Unc **Inclosure Type: Encased Mounting Facility Type And Quantity:** 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 8.0 1st band pass **Functional Terminal Type And Quantity:** 2 turret input 1st function Maximum Dielectric Withstanding Ac Rms Voltage: 100.0 volts at sea level **Specified Frequencies Of Discrimination Per Function:** 2662.00 kilohertz 1st band pass 1st function and 2947.00 kilohertz 1st band pass 1st function and 2530.00 kilohertz 1st band pass 1st function and 3120.00 kilohertz 1st band pass 1st function **Thread Size:** 0.164 inches

Body Material:

Metal

Frequency Band Width Per Function:

382.50 kilohertz 2nd band pass and 467.50 hertz 2nd band pass

NSN 5915-00-930-4440

Band Pass Filter - Page 2 of 2



Discrimination At Specificationified Frequencies Per Function In Decibels:

30.0 1st band pass 1st function and 3.0 1st band pass 1st function and 3.0 1st band pass 1st function and 30.0 1st band pass 1st function **Unpackaged Unit Weight:**

2.000 pounds

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0